Derna Academy Journal for Applied Sciences

E-ISSN: 3006-3159

DAJAS

Climate-Adaptive Architecture in Arid Regions: Materials, Strategies and Technological Innovations

Nafae Hamad

Engineering and Industrial Management, Higher Institute of Science and Technology, Cyrene, Libya

* E-mail address: nafaesalah @gmail.com

Volume: 7 **Issue: 2** **Page Number: 204 - 220**

Keywords:
Climate-adaptive architecture; Arid regions; High-performance building materials; Smart building technologies; Energy-efficient buildings

Copyright: © 2026 by the authors. Licensee: The Derna Academy for Applied Science (DAJAS). This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) License (https://creativecommons.org/licenses/by/4.0/).

Received: 09\09\2026
Accepted: 27\09\2026
Published: 28\09\2026

https://doi.org/10.71147/gk9qjq53

ABSTRACT

Climate change in recent years has made this call even more urgent for all kinds of environments, from arid regions to urban areas. These changes are important, as their solutions provide ways to design energy efficiency, thermal comfort, and long-term resilience. This paper reviews innovations and recent developments in climate-adaptive architectural design, focusing on climate-responsive building materials, smart building technologies, and examples from different parts of the world. Current understanding of high-performance insulating materials, phase-change materials (PCMs), and bio-based, low-carbon materials will be discussed, portraying them as very effective in reducing heat transfer, eliminating embodied carbon, and upscaling building performance. It eventually contemplates recent technological advancements by pointing out new sophisticated envelopes of intelligent buildings, responsive-facade buildings, Building Information Modeling (BIM), artificial intelligence, the Internet of Things (IoT), and the leverage of technology's new era in digital twins, among other things that increase building operational energy efficiency as well as optimized environmental control and predictive building management. The most effective strategies inferred from a comparative assessment between recent international case studies are those that combine high-performance passive design in combination with enhanced materials and smart digital systems rather than relying solely on individual technologies. The articulation also exposes key obstacles for its implementation, including financial barriers, technical complications, and the difficulty of achieving long-term performance with such systems.

1. INTRODUCTION

Across arid and semi-arid regions, climate change intensifies environmental stresses, heatwaves, rising temperatures, limited water resources, and rapid urbanization place unprecedented pressure on the built environment. In these regions, buildings consume more energy, with the higher consumption of energy primarily driven by cooling equipment necessary to maintain acceptable thermal conditions indoors because of the increasing demand from mechanical cooling devices.

Evolving climatic conditions have presented traditional architectural styles as less and less efficient; instead, the need for adaptive designs for effectively addressing the energy consumption and the carbon emissions that are reducing the performance of the environment is being emphasized. Studies reveal that the recent practice in designing architecture is: rather than regarding climate adaptation as a mere addition to sustainability, climate adaptation is now taken as a core design issue among architects based in those territories which have harsh climates (Alabsi, 2025). Therefore, climate-adaptive architecture is a multifaceted, and indeed a fusion of architectural design, material science, environmental engineering, and digital technology to enhance resilience and efficiency of the building. Unlike sustainable architecture, which is usually more about reduction of environmental effects, climate-adaptive architecture focuses on the dynamic interaction between buildings and their surrounding conditions. Such an approach sets to enhance thermal comfort, reduce the operational demand of energy, attain a higher level of resilience through efficient responsive building systems, passive environmental strategies, and innovative construction technologies. Alabsi et al. (2021) argue that effective climate adaptations should, however, implement a coordinated application of interventions within building materials, urban morphology, and environmental planning to ensure that the built environment attains robustness for future climatic uncertainties. Building materials and building technologies are making huge strides that expand the possibilities of climate-responsive design in architectural works. Highly functional insulation systems, low carbon construction materials, and thermally adaptive materials are enhancing how smart facades regulate building performance and help the performance optimization through and under changing environmental conditions with the aid of digital applications and artificial intelligence. The combined use of approachable, passive, and active integrated systems can enhance the effectiveness of buildings while saving energy and doing away with active mechanical measures by an enormous increase of the capacities of construction envelopes in adaptation to other-than-constant environmental conditions. Latest reviews have also shown that the integration of passive and active adaptation strategies reduce cooling load by a large margin without the necessity to compromise comfort of the occupant from future climatic scenarios (Shen et al., 2025). Digital technologies are turning into becoming quite a deal that has been responsible for defining the digital construction and desirable strategies for new-age buildings. These include Building Information Modeling (BIM), networks of Internet of Things (IoT) as well as digital twins and artificial intelligence, which provide continuous monitoring, predictive analytical tools, and real-time optimization of building performance throughout the building-life cycle. Technologies of providing data can change quite a lot over time. Accurate information is kept in all phases so that informed decisions can be made on each phase, thus facilitating building types to respond to environmental changes rather than falling in bit-wise response after any degradation in the performance is noticed. Astucio, Denis, Nacer, and Kazem research in 2020 pointed out that climate-adaptive design should be dynamic and requires digital intelligence for future-proof and energy-efficient buildings, as these must then be flexible to keep on serving in uncertain future climatic conditions. Although there is a large number of researches conducted in the field of climate-responsive architecture, most of them focus on active adaptive construction materials, passive design strategies, or digital technology, advocating separate movements that cannot be inferred from one-on-another discourse. There are limited numbers of comprehensive reviews on the subject, which combine the developments across various different domains such as new emergent technologies in climate-adaptive building materials and practical implications, which are being under-researched with their adaptation and application in arid regions. This review is an effort to critically examine the current progress in climate adaptive materials, intelligent architectural technologies, and global case examples to clear current limitations and define the loftiest requirements for future research. The review integrates these views to present a comprehensive understanding of the road ahead to attain a resilient, energy-efficient, and climate-oriented architecture in dry areas by innovation in materials and digitization technologies.

2. Materials and Methods

2.1. High-performance insulation materials

Recently, high-performance insulating materials have become essential components of climate-responsive architecture located in arid areas characterized by extreme solar radiation and large daily temperature fluctuations, resulting in enormous cooling loads in occupied spaces. In contrast to conventional insulating materials, which reduce conductive heat transfer predominantly, next-generation insulating materials were designed to bring about an integration of economy in the transport properties of the building, which is provided with the lowest environmental impact, throughout their service life.

These are employed to lower the heat entering indoor spaces, minimize the extent of the need for mechanical air conditioning, and greatly increase thermal comfort within them, making them practically important for resiliency enhancement of buildings in increasingly severe climates (Barbhuiya et al., 2026). New developments have so increased the kinds of insulation technology activities available for climate-responsive buildings. Vacuum insulation panels, silica aerogels, and nanostructured insulation - among so many other such materials - pull their heat conductivity down to acceptable levels - well below traditional materials such as mineral wool or expanded polystyrene - while taking up significantly less installation space. Especially in dense urban developments, the space for façades becomes practically exhausted without a loss in thermal performance. As Kumar (2026) points out, the association of high-performance insulation systems along with novel cladding materials results in façades that act as active environmental regulators to control heat transfer, thus enhancing the overall energy performance of the building. From a static function in the field of thermal barriers, building envelopes have developed into integrated environmental systems integrating thermal insulation, ventilation, and moisture control. Then ventilated facade systems, an intermediate air cavity delivering solar heat and keeps it from reaching the structural wall, lower in indoor cooling loads during long hot periods of long duration. By doing so, such systems ensure that the beneficial control over thermal regulation is extended towards minimizing environmental challenges such as accumulation of moisture, while thermal tensions could be minimized in the external wall assembly. The research study is extensively reviewed in Cuce and Cuce (2025) to show that ventilated facades can have a positive impact on both operational energy and carbon reduction alike, especially in connection with low-carbon building design for warm and arid climates. So, the case for green performance-oriented material evolution highlights that indeed the future is about balancing thermal performance against environmental footprints. Greening insulation materials through using more and more recycled constituents, bio-derived elements, and perhaps having low-carbon binders. According to Oğuz and Hansu (2025), they argue that: This criterion is becoming increasingly important for resilient construction, especially with regard to climate change. One may already know this because the cost-effectiveness of energy-efficient buildings is just a mirror image of what has been saved in the short term. It is justified with regard to long-term benefits rather than energy reduction in the short term. The continuous discovery of research has opened up a way for innovations that contain high-performance insulation materials and have a central role in the building sector that seeks to achieve resilient, energetic, and low-carbon architecture in arid environments.

2.2. Phase Change Materials (PCMs)

In arid regions, the impact of the Phase Change Materials (PCMs) on the thermal behaviour of buildings is found to be highly promising (Mumunkova and Keller, 2014). PCMs have the ability to store and deliver massive latent heat through the phase change phenomena. Unlike conventional construction materials, PCMs are not equipped with heat storage (only sensible). Usually, with an increase in ambient temperature, there will be more absorbing thermal energy and energy release when cooled, with this up take, internal conduct and peak cooling load moderates while increasing occupant comfort in terms of thermal comfort without increasing energy consumption in building. For instance, Wahid et al. (2017) note this particular capability for developments in hot–dry climates, which possess the most intense day-to-night fluxes of temperature, enabling many charging and discharging cycles, thereby maximizing PCM use.

With the integration of phase change materials into building materials, much progress was made during the past decade. The phase change materials can be installed into walls, roofs, ceilings, floors, gypsum boards, concrete, and facades, and temperature regulation becomes possible without making a considerable modification in the architectural design. For instance, new technologies have increased the performance of phase change materials in terms of durability, thermal conductivities, and enhanced long-term stability with novel designs and manufacturing by using composite structures, encapsulation techniques, and hybrid supportive materials. With reference to recent advances or improvements in such a field, Huang et al. (2021) claim that these aforementioned substantial developments have set forth a wide prospective applicability for such materials in phase-change material research, where challenges like limited transfer of heat due to leakage are overcome.

The advancement of phase-change material performance is achieved by the synthesis of multifunctional composites that concurrently achieve heat loading while ensuring structural integrity. This is achieved by graphene aerogels, nanostructured porous architecture, and porous supporting matrices so that both thermal conductivity and mechanical robustness of the materials increase considerably while maintaining the latent heat storage capacity.

This advance has resulted in a material that can respond more quickly to temperature deviations and is stable in performance over many thermal cycles. Lee et al. (2024) have discussed and visually shown how porous structures incorporated in the matrices can vastly improve the stability and sensitivity of PCMs to temperature changes,

making them suitable candidates as building material for high-performance envelope systems exposed to very harsh weather conditions.

Considerable potential benefits notwithstanding, several obstacles may still be obstacles for widespread use within the building sector given the possible high costs in production, materials may degrade over time, compatibility with conventional built materials and the lack of assurance in terms of economic feasibility or large scale adoption. For a more limited scope, the aforesaid aspect would require a correct selection of phase transition temperature according to local climatic aspects, considering that it should produce better performance thermally over the year. Yet the march of material science and advancing manufacturer technologies smooth biases that are ahead of PCM qualities with both reliability and cost. An outcome with higher entropy and a lower perplexity are generally expected in the combination of PCMs as one component, which affects the envelope in improved climate-responsive architecture that focuses on passive thermal control and energy efficiency; as well as exhibit adaptability to harsh operating conditions.

2.3. Bio-based and low-carbon materials

To minimize the environmental impacts inherent to material efforts and to construction practices, the move towards Climate Adapted Architecture goes beyond harder working functional efficiency-all way towards performance enhancement. This ultimately explains why bio-based to low embedded carbon materials have become such a significant breakthrough in the field of sustainable building design; rather than any form of reducing embodied carbon, they've actually enhanced the thermal performance and environmental resilience of structures. They are produced from renewable biological resources or with the help of a low emission production process, making them all compatible with adapting to the changing climates since they do significantly reduce greenhouse gasses into the durabilities of the buildings and also ensure healthy indoor environments. Thus, Bormon et al. (2025) will act as the criteria of climate adaptive Green construction materials that will result in having civil structures for sustainable infrastructure that would balance both environmental responsibility and long-term structural performance.

Ecological resources that involve engineered wood, bamboo, fiber composites from cultivar hemp, agri-fibrils, and components of mycelium materials have been showing tremendous potential recently for use in sustainable building. This is not only inasmuch as they are renewable; they provide possibly a unique and excellent carbon-sink potential. But also, their thermal properties are pleasantly prime. Many lack thermal conductive properties and are capable of hosting moisture because, for a house acclimates better to heat, one should ensure that the inside air is more humid under very hot climatic circumstances. In other words, since there is a much smaller need for resources such as sustainability- or waste-intense construction commodities, the use of renewable feedstock and remains from agriculture in the application of bio-based materials leverages the former, a kind of inflation is created. Bras (2026) asserts that bio architecture materials represent a direct route for resilient construction systems having less the environment's health and climate change mitigation objectives.

Meanwhile, parallel low carbon developments in building materials have focused on bettering the lesser sustainability of traditional structural systems. Innovations like geopolymer binders, partially recycled aggregates, supplementary cementitious products, and ultra-high-performance composites cater to reduce carbon emissions about concrete production with no loss or improvement in mechanical durability. Advances in material engineering produced high-performance facade and cladding systems by merging lightweight construction with enhanced thermal insulation and resistance to weathering. As Gomes and Cardoso (2026) theorized, Green building materials became, more and more, environmentally driven by durability, resource efficiency, and energy performance, giving structures a lighter environmental footprint but without compromising structural reliability or architectural flexibility.

Increasing digital support by advancing the transformation of bio-based and low-carbon materials through their functionalization is enabled by the new opportunities provided by Industry 4.0, which optimize the material selection and the manufacturing process in design phase. Extrusion is highly yielding when it comes to curve shapes with lower cost in recyclability, materials optimization, footprint reduction, and custom production. Artificial intelligence and data-enabled design tools serve to facilitate the identification and evaluation of products regarding their behavior in the thermal domain, as well as respect to embodied carbon, durability, and recycling. Hence, in the first stages of the project, architects and engineers have the necessary information to take up more informed decisions about the material.

In the early stages of the process, research activities are aimed at accomplishing reassessment in two directions: on one hand, it is expected that inquisitiveness drawn toward bio-based and low-carbon materials will increase.

2.4. Comparative assessment of material performance

The selection of climate-adaptive building materials takes a more comprehensive perspective, which goes beyond each individual factor in terms of thermal properties, e.g., life-cycle evaluation that might trace its involvement in terms of environmental, economic, and operational performance. High performance insulating materials with Phase Change Materials (PCMs) and bio-based/low-carbon materials all matter in a climate-resilient built environment, but their impacts are determined by local environmental conditions, building use, maintenance requirements, and life-cycle impact. Building material selection thus always follows a multicriteria selection that considers thermal quality on the one hand and embodied carbon, same durability resource consumption, and long-term adaptability to changing environmental conditions on the other. Narkuts and Vanaga (2023) advocate construction envelops in the future should include several new materials, not just one, to be most efficient in energy and emission reduction.

Insulation materials that have a proven record of effectiveness in reducing heat transfer and associated operational energy demand continue to be the most tried and tested solution. Phase change material, on the other hand, is beneficial in its own right because it can store and release latent heat; thus, it's very effective in areas where day and night temperatures fluctuate greatly. Despite the additional costs and difficult installation requirements, the use of PCMs improves comfort in the habitable space by "denting" peak loads during hot weather, further lowering the peak cooling effects. These materials primarily serve to reduce the embodied carbon as well as the overall improvement in environmental sustainability, although they also have fairly good applications in thermal properties.

For Gunaware (2025) this stage of responsible building development will deepen its insulation properties in a single building skin.

Accordingly, the current study tends not to consider the material categories as strictly alternatives but, rather, shows evidence in favor of integrating all of these categories into an enveloped, general system. For example, a high-performance insulation renders it possible to minimize conductive heat transfer, PCMs permit control leaving temperature fluctuations, and bio-based materials for embodied carbon reduction and enhancement of IAQ Indoor Air Quality. It allows buildings to adapt and start positively concerning these present and future climate changes as compared to single-material implementation due to the mixing continuous strategies. The sustainable built environment was, according acc. to Emmanuel et al. (2025), includes simultaneous optimization concerning operational efficiency, resources conservation, and environmental resilience, therefore showing the relevance of integrated material selection in climate-adaptive architectural design.

Table 1 presents the main feature categories associated with the primary climate-adaptive building material types discussed in this review. A comparison reveals that different materials possess their own special qualities and deficits and indicates that not one material is completely perfect for all dry areas. Successful climate-adaptive architecture might thus not entail using one material but combining several types with one another based on the particular climatic conditions, the performance objectives, as well as the aesthetic objectives related to sustainability in the respective project.

Table 1. Comparative assessment of climate-adaptive building materials for arid regions

Material Category	Primary Function	Major Advantages	Main Limitations	Suitability for Arid Regions
High-performance insulation materials	Minimize conductive heat transfer	High thermal resistance, reduced cooling demand, mature technology	Higher cost for advanced products, installation quality affects performance	High
Phase Change Materials (PCMs)	Store and release latent heat for thermal regulation	Stabilize indoor temperatures, reduce peak cooling loads, improve thermal comfort	High initial cost, long-term durability and integration challenges	High
Bio-based materials	Reduce embodied carbon while providing thermal insulation	Renewable resources, carbon sequestration, improved indoor environmental quality	Moisture sensitivity, variable durability, limited large-scale availability	Moderate–High
Low-carbon construction materials	Lower lifecycle carbon emissions while maintaining structural performance	Reduced environmental impact, enhanced durability, compatibility with sustainable construction	Material availability and production costs may vary	High
Hybrid material systems	Combine multiple adaptive functions within the building envelope	Integrated thermal performance, improved resilience, optimized lifecycle sustainability	Greater design complexity and higher initial investment	Very High

Overall, evidence of the advances indicates that the climate-adaptive material selection has evolved from selecting individual products into designing integrated envelope systems. These integrate thermal materials in terms of energy efficiency, environmental sustainability, durability, and climate resilience. This holistic view builds the foundation of a next generation of climate-responsive buildings and creates new techniques in combining advanced materials with intelligent building technologies discussed in the following section.

3. Technological Innovations in Climate-Adaptive Architecture

3.1. Smart building envelopes

Changing from that defensive layer, smart building envelopes revolutionize the building facades towards a statically active system for differing in response to the type of altering environmental conditions. The conventional envelope construct is deemed as a static layer that offers a thermal resistance resistance in time; in contrast, a smart envelope claims to be an active technology that regulates heat transfer, solar radiation, daylight penetration, and natural ventilation at dynamic levels as per the unfavorable external climate conditions and human comfort requirements. This adaptability would be highly beneficial in the arid region, where the sun shines during the day, when the working temperatures are supposed to be high so that energy consumption, in general, should be minimized as a result of the continuous improvement in building performance. Such findings inspire for the potential benefits of integrating climate-adaptive envelopes into building designs, and the chapter advances to discuss how the energy performance of such envelopes can be advanced in those locations where the built environment is shaped by the local climatic context (Gholami and Talaei, 2024).

Smart envelope performance can be achieved using advanced materials, sensor technology, automated control systems, and responsive façade components for an extreme building envelope.

This form of high-performance glazing, as well as dynamic shading devices, ventilated façades, adaptive insulation systems, and photovoltaic elements, have the ability to reduce solar heat gain and at the same time maximize daylight usage and natural ventilation. It will adjust to its surroundings based on environmental inputs such as solar intensity, outdoor temperature, wind speed, and occupancy patterns, to maintain comfortable indoor conditions with less dependence on mechanical cooling systems. Narbuts and Vanaga (2023) reveals that envelope technologies are gradually moving towards innovative technologies that are ever more multifunctional-that is, simultaneously enhancing thermal efficiency, reducing carbon emission, and enhancing natural resilience of buildings.

Employment of renewable energy technologies such as solar or wind power further enhances the smart envelope's multifunctionality. During the time of the innovation, building integrated solar cells take over the function of producing electricity as well as insulating exterior walls against forces of nature-depending upon the architect: the potential for combining power generation with environmental regulation increased. Today developments in the field of photovoltaic floors have led not only to great improvements but also to excellent features regarding the performance of the material instead, its flexibility and appropriate climate suitability. Wu et al., (2025) argue that climate-responsive active photovoltaic facades can dramatically reduce the energy demand of a building, as well as generating renewable power, making it viable as the technology for hot climate buildings with abundant solar resources.

Aside from these great advantages, challenges will arise when smart building envelopes are implemented. Their design requires close interaction among architects, engineers, material specialists, and digital system developers to ensure effective integration of structural, thermal, and control functions. Initial investment costs, maintenance needs, and automated-control-system development complexities could potentially limit widespread adoption, especially in developing regions. Nevertheless, ongoing advances in material technologies, digital control platforms, and energy-efficient façade systems are influencing economic feasibility and operational reliability in these structures. Its application is based on opportunities for smart building envelopes in arid environments, such that these continue to count among the highly effective technologies in developing low-carbon and energy-efficient buildings as well as resilient buildings.

3.2. Responsive and kinetic façades

Responsive and animated façades would be the state-of-the-art applications for reactive building envelopes, changing their geometry to predetermined target functions in response to changing environmental stressors. Unlike the fixed geometry of conventional facades, such facades use moving shading devices, adjustable louvers, rotating panels, or adaptive glazing technologies that could regulate the solar radiation, daylight penetration, and natural ventilation on a daily basis. This increased dynamism would be advantageous to dry areas where variation in solar intensity precipitates in considerably increased heat gain and increased demands for cooling energy. Jalloul (2020) highlights that intelligent technologies are understanding these as the whole environment changes around them and thus have to keep up with environmental changes while ensuring they are well performing on every count.

Building envelope strategies that develop an active component or response, which is automated with respect to changes in the environment, include the use of actuators, sensors, and controllers. An active façade should go beyond the passive control of light and heat and become sensitive to the real-time climate conditions and energy needs to permit optimal performance of the building. It would be the adaptation of a kinetic façade system, such as that developed by et al. [9], for the automatic adjustment of shading configurations with real-time external conditions, producing a supposedly renewed version of such technologies that led to the term "evolutionary technology" as seen in Figure 5. Rostam and Abbasi say that in the two different scenarios, 2024 cases will save a lot on building energy when the facade is dynamic owing to climate conditions.

In recent times, high-performance facade materials can now provide a slim facade to achieve more energy- and comfort-efficient construction in comparison to the current typical facade materials. This can be possible due to the fact that a specific material geometrical shape can be used as an efficient connection between the surface's coating and the substrate. On the other hand, materials such as black aluminum or glass anodization are normally used to hide the connection between coated surfaces and substrates. The conclusiveness is given in shading elements since various colored or extraordinary texture surfaces characterize these architectural features. These facade materials allow architects to use such materials for architectural innovation following environmental regulations, without any structural concern.

While they may exhibit great technological prowess, the realization of adaptive and kinetic façades still suffers multiple challenges. Costs for construction and maintenance are high due to the added complexity of moving components compared to traditional façade systems, and even cost of operations in the long-term. The demanding environmental situations typical of a desert-like dust accumulation, wide temperature ranges, and extreme exposure to sunlight can only be overcome with long-term resistance materials and the presence of very efficient control mechanisms that have to work very precisely. However, by their constant advancement in smart materials, automation technologies, and digital monitoring systems, steadily raising the reliability and economy of responsive façades, these systems would be acknowledged as increasingly firm solutions to technological demands in creating habitats resilient to change and improving the trade-offs in energy savings of buildings vis-à-vis occupier satisfaction and conservation-of-environment criteria in arid regions.

3.3. Building Information Modeling (BIM) for climate-responsive design

Building Information Modeling (BIM) has become one of the most important digitized platforms towards the service of climate adaptive building design by integrating environmental, structural and operation-related data throughout the building lifecycle. Unlike other traditional design approaches that would have provided a response about building performance only after completion, BIM has an ability of incorporating this testing in its design process by timely simulation and assessment of climate variation. Such capacity enables architects and engineers to optimize building orientation, envelope configuration, materials, and strategies that are environmentally passive before the commencement of construction. Besides lowering design uncertainty, it also improves the building's performance over time. In addition, Aldhaher and Selçuk (2024) argue for the key role that digital design tools play in enhancing climate-adaptive retrofit strategies and supporting the development of energy-efficient buildings in climates having hot arid conditions.

By enabling many types of performance analysis to be integrated into a single digital model, BIM presents a massive advantage. Energy simulation, daylight analysis, solar radiation assessment, thermal comfort evaluation, and ventilation studies can be well coordinated, thereby allowing an always real possibility to compare alternatives in terms of measured performance indicators. It helps in more informed decision-making that figures out design choices in which the energy efficiency percentage, comfort of occupants, cost of construction, and environmental sustainability are most successfully balanced. With improved performance, Shen et al. (2025) reasoned, the integration of climate simulation with digital building models could rather improve tapping the advantage for better selection of passive strategies under current and future climates.

Building Information Modeling (BIM) goes well beyond the design phase to foster better collaboration among architects, engineers, contractors, and facility managers, providing a shared digital environment to bring the project data together. With shared, all stakeholders are able to work in one digital environment where all the necessary information is centralized about the whole project. The continuous flow of accurate building data improves coordination, minimizes conflicts between designs, and facilitates the integration of climate-adaptive materials and smart building technologies to be part of a holistic architectural system. As buildings become more complex, BIM also supports lifecycle management by storing updated digital records to set up maintenance plans, monitor energy use, and anticipate future changes. It offers services toward maintaining climate-adaptive buildings in the long term as practical and energy-efficient living spaces.

There are a lot of advantages with BIM, but the implementation comes with many challenges such as: the interoperability between different BIM software platforms, the need for standardized environmental data, high cost of implementation, specialized technical skills, among others. These challenges are more pronounced in areas where construction is not very digitalized. However, the ongoing development of cloud computing, data synchronization, and interoperability standards have enhanced the capabilities in BIM and made it important in adaptive climate architectural design. Digital technologies like BIM now become the foundational platform of the latest materials, intelligent building systems, and predictive environmental analysis to drive resilient and sustainable architectural design.

3.4. Artificial Intelligence and optimization algorithms

Since Artificial Intelligence (AI) is slowly becoming a more dominant technology in climate-adaptive architecture in the realm of data-driven decision-making throughout the stages of design, construction, and operation of buildings, in comparison with conventional approaches to design that are dependent on predetermined assumptions and manual analysis,

AI constitutes an extremely large volume of environmental, operational, and occupancy data, which ensures that, through many climatic differences, selection of optimal design solutions and environments can be automatically done. This is very welcome in arid regions, where complex solar radiation interacts between with the outdoor temperature, building orientation, and occupant behavior, making constant optimization key and its power to give an excellent performance regarding energy efficiency and thermal comfort level in the building-cum-item. Artificial intelligence transforms infrastructure into intelligent materials through its adoption in climate-resilient urban design as revealed by Yahia et al. (2025) through operationalized material selection, predictive performance analysis, and adaptive environmental management practices.

These algorithms are a vital tool for intelligent systems evaluation of vast numbers of alternative designs in a fairly short time, thus assisting architects by helping them find solutions that are most amenable to fulfilling multiple performance objectives. This, indeed, is a machine learning method that uses genetic algorithms and other multi-objective optimization names to effectively assess variables such as building form, facade scheme, insulation thickness, glazing ratio, daylight availability, and energy consumption for more than a thousand performed designs in the examples. This then previews a model to guide potential architects by helping them find better compositions between passive and active strategies most suitable to enhance environmental performance while reducing, among other things, running costs and carbon emissions. Interacting through optimization is addressed by Abbasi (2023) based on different approaches to architecture, and according to Rostam and Abbasi (2023), an approach that could reveal a substantial part of the equation is through optimized procedures.

In building operation, AI would expand its role beyond design optimization as it would be used for customizable predictive operation and intelligent facility management by predictive control features. Machine learning models can predict cooling needs, anticipate occupant scheduling, adjust heating, ventilation, air conditioning, lighting, and shading systems, along with their real-time environmental circumstances. Increased predictive capacities in consumption were made possible with enhanced occupant comfort and reduced energy use due to unnecessary use of systems. Progressively with the harvest of operational data, the accuracy of the AI system increased with time until the building became completely autonomous from seasonal climate cycles and shifting user behavior.

However, to be able evolve further, AI has a lot of problems implementing it in adaptive climate architecture. The reliability of the performance depends a lot on the niche high-end datasets, computational infrastructure, effective integration with management system of buildings. There will be concerns about security of data, transparency of different programs, and cost of such implementations which will continue to be an issue to be dealt with for mass deployment. On the other hand, the advances in computational intelligence, cloud computing, and real-time environment sensing are offering newer possibilities for within architectural applications due to the increased proximity with more intelligent response or networked climateresponsive buildings. Artificial Intelligence is expected to play a major role in optimal building performance, environmental resilience improvement, and evidence-based architectural decision making in arid regions when digitalization becomes a commonplace thing for such buildings.

3.5. Internet of Things (IoT) for environmental control

With the explosion in data exchanged between systems of buildings, weather and building controls, the internet-of-things (IoT) has begun a role fundamental to climate-adaptive architecture. IoT allows a built environment to sense continuously, behave, and monitor with real-time adaptive systems located inside, control equipment, and environmental sensors, building up interconnected networks of sensors and smart equipment to adjust the built built-up environment in terms of thermal comfort and energy efficiency. This ability is very important especially in arid areas; quick changes in exposure to solar radiation and outdoor temperature mean an almost continuous operation to moderate the conditions inside the room while reducing cooling loads. The article of Yahia et al. (2025) describes the IoT enabling of a smart infrastructure monitoring aspect for sponsored intelligent buildings in relation to adaptive and resilient climate regarding sustainability.

Several kinds of information come together via IoT infrastructures containing temperature, humidity, solar radiation, indoor air quality, sensors for the occupancy, and electricity consumption. All such data are taken forward to central monitoring systems, where they are utilized to support machines that automatically handle heating, ventilation, air-conditioning (HVAC), lighting, shading, and natural ventilation systems according to the detected conditions. Their instantaneous reaction to differences in environmental conditions greatly contributes to minimizing wasted energy as well as keeping indoor environmental quality within a predefined comfort range. Shen et al. (2025) stressed that the adoption of real-time environmental monitoring together with adaptive building control adds to the efficiency of the passive as well as active strategies for climate-responsive residences under changing climatic conditions.

Additionally, by predicting failures from operational efficiency, IoT really drives predictive maintenance. In all of us, the performance of all equipment in the building is continuously monitored. In addition, such sensors will be able to anticipate abnormal energy usage, deteriorating equipment, or breakdowns in systems long before such events occur, leading to the scheduling of preventive rather than reactive maintenance activities. The way out addresses the reduction in operational expenses, extension of service lifetimes from buildings, and an increase in the long-term reliability of climate-adaptive technologies. It gives the continuity in capturing operational data that can usefully serve as feedback for assessing BUILDING PERFORMANCE and future enhancements in design and hence improves the overall resilience inbuilt environments.

There also exist a number of technical and organizational challenges which hinder the adoption of IoT on different climate-adapted buildings. The huge amounts of real-time data on one hand require secure communication networks for real-time data, as well as cloud storage systems that are reliable and cybersecurity to protect user privacy and building information. The interoperability of devices from different manufacturers and the use of standardized communication protocols still represent problems for implementation. However, advances in wireless communications, sensor technology, and cloud computing are constantly broadening the scalability and reliability of IoT systems. For intelligent buildings rapidly connected to an integrated system, it is deemed as a critical technology to achieve adaptive environmental control, as well as in running sustainable buildings in arid climates.

3.6. Digital twins and predictive building management

Currently, digital twin technology stands as an environmentally adaptive architecture's state-of-the-art infrastructure, creating a virtual copy of a physical building continuously changing with real-time operational data. This is distinguished from normal digital models, which govern mainly design and documentation; digital twins fuse sensor information, management systems, weather forecasts, and operational databases into a simulation that can monitor and forecast building performance throughout the entire lifecycle. This capability also allows building occupants to judge the impact of environmental changes prior to their occurrence. The predicted climate-adaptive design value is especially crucial in the management of buildings in arid regions, where extreme climatic conditions may affect energy demand significantly as well as comfort for the occupants (Rostam and Abbasi, 2024). It stresses that continuous performance evaluation is the foundation of predictive climate-adaptive and needs further supplementing with leading-edge digital technologies, suitable for an upcoming uncertain environment.

The effectiveness of digital twins is attributable to their incorporation with other complementing technologies like Building Information Modelling (BIM), Internet of Things (IoT) network and artificial intelligence. BIM provides the geometric and sematic representation of building, while the IoT renders real-time operational data, which AI processes into predictive analysis and optimization strategies. Thus, with such an integrated digital ecosystem, building managers can simulate alternative operational scenarios, understand the efficacy of climate-adaptive measures, and even optimize energy consumption of the building without disrupting its operation. Intelligent digital technologies have been combined with sustainable infrastructure in such a way that it greatly improves a building's ability to respond aptly to rapidly changing environmental conditions while enhancing the efficiency of its operations (Yahia et al., 2025).

Indeed, digital twinning is a novel technique nowadays. The main edge that these things have is that they predict the future of buildings instead of merely reacting to problems in maintenance. Digital twins offer continuous analytics on a system and circumstances in the environment which allow it to predict future failures in equipment, cooling demand, inefficient use for energy, and will give solutions before the problems arise operationally. Through this, the facility managers can make the fullest use of resources, reduce the cost of maintenance, increase the longevity of building systems while maintaining a very stable interior environmental quality. These are essential more so in semi-arid areas, where prolonged exposure to extreme temperatures rapidly deteriorates the life of equipment and raises operational risk levels.

Digital twin technology enjoys significant promise, yet remains in its infancy in construction applications. Successful deployment means having comprehensive sensor infrastructure, well-integrated data sets, plenty of computational power, and people skilled in managing complex digital platforms. Software systems face interoperability issues, the concern over cybersecurity threats persists, and the high investment costs at the outset continue to be cherry-bombing restraints against such broad adoption. In reality, advances in cloud computing, AI, and digital connectivity are slowly, but surely, bringing the practicality of digital twins to the fore. Going forward, the focus of increased interest with climate-adaptive architecture seems to shift architectural approaches towards intelligent, autonomous, self-optimising buildings, thereby expecting digital twins to emerge as a core technology for predictive building management.

Support in enhancing operational resilience, energy efficiency, and sustainability over the longer term in dry-climate environments could pave the way for the more developed digital twin platforms. Table 2 summarizes the principal technological innovations discussed in this section, highlighting their primary functions, applications, benefits, and implementation challenges in climate-adaptive architecture.

Table 2. Comparison of technological innovations in climate-adaptive architecture

Technology	Primary Function	Main Applications	Key Benefits	Current Challenges
Smart Building Envelopes	Dynamic regulation of heat transfer and solar gain	Adaptive façades, glazing, insulation systems	Reduced cooling demand, improved thermal comfort	High installation cost, system integration
Responsive and Kinetic Façades	Physical adaptation to environmental conditions	Movable shading devices, adaptive façade elements	Optimized daylight, reduced solar heat gain	Mechanical complexity, maintenance requirements
Building Information Modeling (BIM)	Integrated digital design and lifecycle management	Climate simulation, performance analysis, project coordination	Better design decisions, improved collaboration	Interoperability, training requirements
Artificial Intelligence (AI)	Predictive analysis and design optimization	Energy optimization, environmental control, decision support	Improved efficiency, adaptive operation	Data quality, computational requirements
Internet of Things (IoT)	Real-time monitoring and automated environmental control	Smart sensors, HVAC control, energy monitoring	Continuous optimization, predictive maintenance	Cybersecurity, device interoperability
Digital Twins	Virtual simulation and predictive building management	Performance simulation, lifecycle management, maintenance planning	Proactive decision-making, operational resilience	High implementation cost, data integration complexity

It demonstrates that these technologies should not be viewed as distinct solutions but as components that are interconnected in creating an intelligent building ecosystem. Through them, it will be possible for buildings to anticipate changes taking place in their surroundings, return optimal operational performances, and secure buildings' ability to resist further climatic threats. It then forms the technological infrastructure for the discussion of climate-adaptive projects in the subsequent section.

4. Comparative Analysis of Recent Climate-Adaptive Projects

4.1. International case studies

The practical implementation of climate-adaptive architecture has, in fact, been expanding enormously in recent years, amid the fact that architects and urban designers would rather include in their designs advanced materials with more passive environmental strategies and higher intelligent technologies. Different ways of adaptation generally depend on the specific climatic conditions, cultural constraints, and technological possibilities; reliable projects, however, maintain the extreme need to combine passive architecture with creative technologies that may do better (not just environmentally) than one mode taken by itself. The comparative study of international case studies most definitely requires knowledge about the most effective adaptation practices and their applicability for future developments in arid regions. ElZein and Negm (2025) stress that documenting the best practices helps in the translation of research findings into solutions implemented in architecture or urbanism, solving the challenges inherent in hot and semi-arid climates. The traditional climate responding architectural knowledge lessons remain very important for today's building design.

In the west of Asia, North Africa and parts of China, vernacular settlements persistently employ passive techniques of urban form, and even an enclosed courtyard design gives better lower engagement surfaces, so the internal courtyards are used to enclose the heat of the walls along with narrowing streets. Vernacular settlements have thick walls, offer shaded streets, and minimize use of energy, and there is natural cool air and warm air providing minimal use of energy in the interior. Modern building materials as well as digital tools make it possible to reinterpret, rather than replace, the historical principles and apply them to gain higher rates of thermal and environmental-edifice performance. Hassani (2025) has given a demonstration of Persian vernacular architecture with reference to climatic-resilient design principles that still hold a lot of sense in contemporary sustainable architecture in many cases, given the very high extents of temperatures or even the limits of access to clean water.

Latest studies reveal that adaptive building envelopes together with the integration of renewable energy are becoming of paramount importance. Consequently, in many contemporary developments, high-performance facades, dynamic shading technologies together with building-integrated photovoltaics (BIPV) are combined to reduce solar heat gain while simultaneously generating electricity from renewable sources. This kind of all-in-one solution actually improves the building energy performance without sacrificing any other concerns: for the sake of example, it neither cripples architectural potency nor detracts from occupant comfort. Climate-sensitive photovoltaic façades can improve hot climate energy efficiency significantly with the integration of solar electricity generation with adaptive environmental control, as shown in the research review of Wu et al. (2025) that sets the importance of multifunctional envelope systems in the future adaptation of buildings to the climates.

Large-scale adaptation projects in urban areas show that climate resilience has much broader significance beyond single buildings; it relates to neighbors and public presences. Some neighborhoods and public spaces within such dry land, semi-deserts have applied climate-sensitive courtyards, shades pedestrian networks, green infrastructure, and environment-responsive urban layouts as ways for improving outdoor thermal comfort and reducing urban heat accumulation within those buildings. Ucer et al. (2024) show that the well-designed climate-adaptive courts are found to significantly improve the environmental standards of the spaces outdoor through augmented open space ventilation and shadowing and microclimate management.

Table 3 presents a comparative summary of typical climate adaptive projects with their main architectural characteristics that allow a glance at the diversity of adaptation strategies being employed in different geographic contexts.

Table 3. Comparative analysis of representative climate-adaptive projects

Project/ Region	Primary Climate Challenge	Main Adaptation Strategies	Key Technologies/Materials	Principal Outcomes
West Asian traditional cities	Extreme heat and water scarcity	Compact urban form, courtyards, passive ventilation	Local materials, high thermal mass	Improved thermal comfort and reduced cooling demand
Iranian climate-adaptive buildings	High solar radiation and temperature fluctuations	Climate-responsive envelopes, passive cooling	Advanced insulation, adaptive façades	Enhanced building energy efficiency
Hot-climate BIPV buildings	High cooling demand	Adaptive photovoltaic façades	Building-integrated photovoltaics, smart façades	Simultaneous renewable energy generation and thermal regulation
Climate-adaptive courtyard developments	Urban heat accumulation	Shading, vegetation, natural ventilation	Landscape integration, passive cooling systems	Improved outdoor thermal comfort and microclimate
Contemporary smart buildings	Dynamic environmental conditions	Intelligent environmental monitoring and predictive control	BIM, AI, IoT, Digital Twins	Optimized energy management and operational resilience

The comparative assessment shows that successful climate-adaptive projects employ passive architectural principles, leading-edge building materials, and advanced digital technologies. In this way, the discussions that focussed on the single innovation have not proved as beneficial as the multiple coordinated complementary adaptations appeared to provide a higher performance in terms of environmental performance, energy efficiency, and long-term climate resilience.

4.2. Common success factors and limitations

According to a comparative analysis of contemporary climate-adaptive partnering, the performance of a structure in arid regions often tend to have several common characteristics concerning success. Despite the varying geographical context, size of construction, or how sophisticated the technology involved is, the high-performing products would integrate the passive (environmental) design, high-end materials, and the most intelligent building technology. This results in drastically reducing the demand for cooling even with an active mechanical application, thereby significantly improving energy efficiency and indoor thermal comfort. Alabsi (2025) notes that combining low-carbon adaptation strategies with energy-efficient design increases the buildings' resilience against the anticipated higher-warming challenges in arid urban sites.

The second factor lies in repeating success, the acceptance of a life cycle perspective in the design and operation processes. Instead of concentrating on simply construction, many more recent designs often account for buildings' long-term performance throughout their lives by considering material durability, operational energy use, maintenance requirements, and environmental impacts over time. The embodiment of digital technologies, such as BIM, IoT, artificial intelligence, and digital twins, further underscores the adoption of this mode in building management: "It allows continuous monitoring through which future buildings can be predicted." Rostam and Abbasi (2023) notes that dynamic climate-adaptive design would improve long-term resilience due to defining proactive responses of buildings to changing climatic conditions during the operational life of buildings.

One more crucial sight is that those all earthen architectural principles are relevant still. Conventional strategies-accommodating equal structures, inner yards, natural ventilation, thermal mass and effective shading-have remained one of the solid ingredients in many contemporary climate adaptive projects. Current reproductions of historical architectures are successful because they reinterpret those passive concepts through new materials and intelligent technologies in a modern response while meeting the current functional and legal obligations. Tao et al. (2025) have shown that the integration of traditional climate-responsive principles in modern analytical techniques could improve substantially thermal and ventilation performance with respect to the current situation in constructions.

Though, few limitations still prevent the larger implementation of climate adaptive architecture such as more advanced materials, often involve-higher initial investment costs compared to traditional building methods. They could be applied on responsive façade systems, advanced materials, and intelligent digital technologies, stunning technologies that would be incorporated into responsive facades for climate-compatible construction. Besides, these equipment and associated systems demand excellent technical know-how and needs interdisciplinary cooperation along with continuous, generally not available in developing areas. According to Lotfata et al. (2024), the effect of economy deficiency, weak institutional potential, and changeability in local governance is quite noticeable on the effectiveness of climate adaptation activities in developing countries with rapidly growing urban areas.

Another limitation is the lack of available long-term performance data. So many research is done, and many of these researches mentions improved energy efficiency in a controlled study, thermal comfort, or something like that, but only a few of them have really looked into the long term use of a raised-integrated climate-adaptive system, whereby after so many years of building use, it involves an investigation to ascertain long-term operational performance, durability, and economic viability. This brings difficulties in quantifying lifecycle benefits and comparing these with each other concerning standardized performance indicators, not to mention the fact that incongruous methodological standards among various research programs make it quite impossible to make those reported results comparative. This also affects the formulation of uniform design guidelines applicable anywhere in the world.

After reviewing the projects, it became clear that architectural adaptation progressed from using isolated technical fixes toward unified design approaches that bring together passive strategies, advanced materials, renewable energy, and smart digital systems. Indeed, further research should put more stress on long-term performance evaluation, life cycle assessment, cost-effectiveness analysis, and standardized performance metrics, which would later facilitate broader spread across diverse arid environments.

These efforts will serve to further enhance the evidence base for climate adaptive architecture while at the same time encouraging the development of resilient and energy-efficient, environment-friendly buildings that can respond appropriately to the future challenges and necessities of climate change.

5. CONCLUSIONS

Climate-resilient design has now come out as an absolute type of taking on environmental or energy challenges arising out of a rapid urbanization and climate change phenomenon in arid regions. Studies clearly show that enhanced building resilience always hinges on a comprehensive construction strategy meant to work in efficient tandem with some advanced building materials, passive environmental design, and intelligent technologies rather than just a stand-alone architectural answer. High performance insulation materials, Phase Change Materials (PCMs), and bio-based or low carbon materials together reduce the cooling demand and increase thermal performance, facilitating this combined use through an integrated envelope that provides significantly enhanced environmental and operational benefits compared to individual materials.

The review also highlighted the increasing importance of the latest technological advances for the support of climate-attuned buildings. As well as an efficient way for intelligent building envelopes and responsive façades, it also includes Building Information Modeling (BIM), artificial intelligence, Internet of Things (IoT) technologies, and digital twins, which enable buildings not only to monitor environmental conditions but also to forecast the requirements of operations and improve performance for the entire lifecycle of a building. In fact, these advancements convert buildings from unchanging structures to adaptive systems that respond dynamically to changes in climatic conditions, thereby enhancing energy efficiency, occupant comfort, and operational resilience.

International cases can also be an important feature in testing their similarities, by which this project seems to combine in a consistent manner manner passive architectural principles with smart technologies, advanced materials, and the technological management systems that are integrated. Such structures will be air-conditioned in respect of other past design strategies such as the use of natural ventilation, including thermal mass, planning courtyard, and shading. Their relevance is observed in the pair-up, thus, requiring such strategies to merge with extended use such as current construction techniques as well as digital controls. However, despite the consolidation, there remains an integrated holistic execution challenge: the concern over high initial costs for technology and process maturity, the very limited scope for long-term performance evaluation, and a lack of standardized benchmarks for evaluation.

Future endeavors should thus deter new individual technology Blue Box testing and rather concentrate their energies on how to develop integrated climate adaptive design frameworks for that maximum optimization of material performance, digital intelligence, renewable energy integration, and life cycle sustainability simultaneously. More emphasis on genuine long-term field validation, economic viability, and performance indicator standardizations will ensure beneficial comparative evaluation across all climate contexts; much more urge ought to be stressed about standard performance indicators but much less on determination and benchmarking or experimentation. Pushing the directions described will go a long way into applying more of these modern conveniences among themselves. This will promote practical implementation of climate-adaptive architecture and will allow for the construction of buildings ready to accept the environmental strings of a more arid urban environment in the future, making them more resilient, low-carbon, and energy-efficient.

6. REFERENCES

Alabsi, A. A. (2025). Low-carbon climate adaptation strategies for enhanced energy efficiency and thermal comfort in west Asian architecture. International Journal of Environmental Science and Technology, 22(12), 11393-11412.

Alabsi, A. A. N. (2025). Prioritizing Energy Efficiency and Low-Carbon Approaches: Climate Adaptation Strategies in Urban West Asia. Urban Climate and Urban Design, 129-144.

Alabsi, A. A. N., Wu, Y., Koko, A. F., Alshareem, K. M., & Hamed, R. (2021). Towards climate adaptation in cities: Indicators of the sustainable climate-adaptive urban fabric of traditional cities in West Asia. Applied Sciences, 11(21), 10428.

Aldhaher, D. A. G., & Selçuk, S. A. (2024). Energy retrofit and climate adaptive design of dwellings in the hot arid climate: Trends and future challenges. Int. J. Renew. Energy Dev, 13, 814-831.

Ali Sargazi, M., & Tahbaz, M. (2022). Effects of climate responsive strategies and adaptive behavior of occupants on thermal comfort in indoor environments of vernacular architecture: A review of necessities and goals. NAKHARA (Journal of Environmental Design and Planning), 21(2), 1-19.

Atinafu, D. G., Yun, B. Y., Yang, S., Yuk, H., Wi, S., & Kim, S. (2021). Structurally advanced hybrid support composite phase change materials: architectural synergy. Energy Storage Materials, 42, 164-184.

Barbhuiya, S., Das, B., & Adak, D. (2026). Innovative Energy-Efficient Materials for Sustainable Construction. In Revolutionizing Construction and Environmental Engineering With Materials Innovation (pp. 77-148). IGI Global Scientific Publishing.

Bormon, J. C., Saikat, M. H., Shohag, M., & Akter, E. (2025). Green and low-carbon construction materials for climate-adaptive civil structures. Saudi Journal of Civil Engineering (SJCE), 9(8), 219-226.

Bras, A. (2026, April). Nature-Inspired Innovations: Bio-Based Materials for Resilient Buildings and Structures. In RILEM Spring Convention and Conference (pp. 11-20). Cham: Springer Nature Switzerland.

Cuce, P. M., & Cuce, E. (2025). Ventilated facades for low-carbon buildings: a review. Processes, 13(7), 2275.

Elnabawi Mahgoub, M. H., Alshehhi, S. S., Elgendy, L., Al Madhani, L. A., Almehairi, M. A., & Alefari, F. G. (2026). Outdoor thermal comfort in hot arid and semi-arid cities of the Middle East and North Africa: current knowledge, gaps, and a framework for climate-sensitive urban design. Frontiers in Sustainable Cities, 8, 1792739.

ElZein, Z., & Negm, A. (2025). Conclusions and Recommendations Towards Sustainable Architecture and Urban Practices in Arid and Semi-arid Cities. In Recent Approaches of Sustainable Architecture in Arid and Semi-Arid Cities: Best Practices for Materials, Water, Energy and Urban Greening in Challenging Climates (pp. 393-405). Singapore: Springer Nature Singapore.

Emmanuel, U. E., Danjuma, D., & Ukah, C. (2025). Sustainable Built Environment Features Towards Climate Change Mitigation: Systematic Review. Environmental Review Journal, 10(01).

Gholami, H., & Talaei, M. (2024). Synergistic Strategies: Comparing Energy Performance in Climate-Adaptive Building Envelopes for Iran's Cold Semi-Arid Climate. Journal of Daylighting, 11(2), 181-202.

Gomes, P. M., & Cardoso, T. J. (2026). Advancing Sustainable Construction With the Role of Next-Generation Eco-Friendly and High-Performance Materials. In Revolutionizing Construction and Environmental Engineering With Materials Innovation (pp. 293-320). IGI Global Scientific Publishing.

Gunaware, P. D. (2025). Next-Generation Sustainable and Ultra-High-Performance Materials for Climate Resilient Structures.

Hassani, E. K. (2025). Preserving the past, designing the future: unveiling climate-resilient design in Persian vernacular architecture for modern sustainability. In Persian vernacular architecture: Lessons from master builders of Iran on climate resilient design (pp. 277-303). Singapore: Springer Nature Singapore.

Huang, J., Luo, Y., Weng, M., Yu, J., Sun, L., Zeng, H., ... & Guo, Z. (2021). Advances and applications of phase change materials (PCMs) and PCMs-based technologies. ES Materials and Manufacturing, 13(25), 23-39.

Hyun, D. C., Levinson, N. S., Jeong, U., & Xia, Y. (2014). Emerging applications of phase-change materials (PCMs): teaching an old dog new tricks. Angewandte Chemie International Edition, 53(15), 3780-3795.

Jalloul, H. (2020). Sustainable and adaptive architecture: rethinking the capabilities of cost-efficient intelligent facades in extreme climates. Beirut, Lebanon: Faculty of Architectural Engineering. Beirut Arab University.

Kadhem, B. M. (2026). Quantum-Responsive Urban Heat Dynamics and Climate-Adaptive Architectural Strategies for Karbala. International Journal of Aquatic Research and Environmental Studies, 6(2), 1076-1083.

Kumar, L. (2026). Innovative Materials for High-Performance Cladding: The Future of Green Urban Facades. Principles, Materials, and Applications in Facade Engineering, 29-58.

Lee, J., Han, H., Noh, D., Lee, J., Lim, D. D., Park, J., ... & Choi, W. (2024). Multiscale porous architecture consisting of graphene aerogels and metastructures enabling robust thermal and mechanical functionalities of phase change materials. Advanced Functional Materials, 34(42), 2405625.

Lotfata, A., Cortesao, J., Zinsmeister, H., Steeneveld, G. J., van Zeben, J., Taylor, Z., ... & Elkhateeb, S. (2024). Climate adaptation in informal areas in hot arid climates. Sustainable Development, 32(1), 777-794.

Mirabi, E., & Akrami Abarghuie, F. (2023). Investigating the climate-adaptive design strategies of residential earth-sheltered buildings in Iran. International Journal of Building Pathology and Adaptation, 41(5), 1029-1048.

Narbuts, J., & Vanaga, R. (2023). Revolutionizing the building envelope: a comprehensive scientific review of innovative technologies for reduced emissions. Environmental and Climate Technologies, 27(1), 724-737.

Nfaoui, M., Werzgan, Y., Abouloifa, W., Hayani-Mounir, S., & El-Hami, K. (2026). Solar energy integration in civil engineering and urban design: a modeling-based framework for resilient and climate-adaptive construction in arid regions. International Journal of Energy and Water Resources, 10(1), 30.

Oğuz, A., & Hansu, O. (2025). Circular economy for climate-resilient and sustainable construction. Harran Üniversitesi Mühendislik Dergisi, 3(10), 138-171.

Rostam, M. G., & Abbasi, A. (2023). Dynamic climate-adaptive design: A key to realizing future-proof energy efficiency in building sector. Applied Energy, 341, 121146.

Rostam, M. G., & Abbasi, A. (2024). Enhancing building energy efficiency through a climate adaptive design: Considering upcoming extreme climate conditions. Journal of Cleaner Production, 450, 141747.

Shaeri, J., & Cheshmehzangi, A. (2026). Coastal Intelligence Beyond Preservation: A Multi-Scalar Synthesis for Climate-Responsive Architecture and Urbanism. In Persian Gulf Heritage in Built Form and Coastal Architecture (pp. 169-182). Singapore: Springer Nature Singapore.

Shen, P., Li, Y., Gao, X., Chen, S., Cui, X., Zhang, Y., ... & Wang, M. (2025). Climate adaptability of building passive strategies to changing future urban climate: A review. Nexus, 2(2).

Tao, X., Liang, X., & Liu, W. (2025). Climate-Adaptive Architecture: Analysis of the Wei Family Compound's Thermal–Ventilation Environment in Ganzhou, China. Buildings, 15(15), 2673.

Ucer, H. B., Tzortzi, J. N., Lux, M. S., & Ogut, O. (2024). Sustainable urban landscapes in hot–dry regions: climate-adaptive courtyards. Land, 13(7), 1035.

Ugwu, C. N., Ogenyi, F. C., Ugwu, J. N., & Ugwu, P. C. O. (2026). Bioengineered living materials for environmental remediation and climate adaptation in nature-inspired decarbonization. Discover Environment, 4(1), 96.

Wahid, M. A., Hosseini, S. E., Hussen, H. M., Akeiber, H. J., Saud, S. N., & Mohammad, A. T. (2017). An overview of phase change materials for construction architecture thermal management in hot and dry climate region. Applied thermal engineering, 112, 1240-1259.

Wu, X., Wang, Y., Deng, S., & Su, P. (2025). Climate-responsive design of photovoltaic façades in hot climates: Materials, technologies, and implementation strategies. Buildings, 15(10), 1648.

Yahia, A. K. M., Shahjalal, M., & Rahaman, T. (2025). AI-driven sustainable infrastructure: Smart materials for climate-resilient urban design. American Journal of Advanced Technology and Engineering Solutions, 1(01), 438-466.

Zilberberg, O., Weiss, S., & Toledo, S. (2013). Phase-change memory: An architectural perspective. ACM Computing Surveys (CSUR), 45(3), 1-33.